

MATCAVI S.R.L.

 VIA ANDOLFI, 10 - 80045 POMPEI (NA) - ITALY
 TEL. +39 081 8612740 - FAX +39 081 5364557
 www.matcavi.it info@matcavi.it
 P.IVA IT 02513681219


DATA SHEET- Charging Cables

Rev.2 - 05/2023

CODING OF CHARGING CABLES

CC M 16 T1 T2 _5	<p>CC: Charging Cables</p> <p>CCS: Charging Cables Comoulded</p> <p>M: Phases (M: Single T: Three)</p> <p>16: Rated current (16: 16A 32: 32A)</p> <p>T1T2: Connector type T1: Type 1 T2: Type 2 SC: Schuko Xx: Special request</p> <p>_5: Cable lenght (from 2 to 30 meters)</p>
-------------------------	--

CABLES		TYPE	
		Single phase	Three phases
RATED CURRENT	16A	07BQ-F 3x2,5 + 0,75 mm² Max 3.6KW	07BQ-F 5x2,5 + 0,75 mm² Max 11KW
	32A	07BQ-F 3x6 + 0,75 mm² Max 7.2KW	07BQ-F 5x6 + 0,75 mm² Max 22KW

With the respect for your customers and in order to guarantee the best products quality, MATCAVI is always looking for continuous improvement and the most performing components. Therefore, the above characteristics and components are indicative and can be changed without notice.

MATCAVI S.R.L.

VIA ANDOLFI, 10 - 80045 POMPEI (NA) - ITALY
TEL. +39 081 8612740 - FAX +39 081 5364557
www.matcavi.it info@matcavi.it
P.IVA IT 02513681219



CONNECTOR TYPES

TYPE 2



**STANDARD: IEC 62196-2
CO-MOULDED**

Mennekes Type
European Standard

CARATTERISTICHE PRINCIPALI

- Cable resistant to abrasions, oils and chemicals
- Smooth and matte surface
- Ergonomic handle
- Comfortable contact surface
- Suitable for all types of electric vehicles and charging stations on the market
- Made of high strength ABS
- Contacts tested up to 50,000 cycles
- Protection degrees: IP 65 mated with protection cap



With the respect for your customers and in order to guarantee the best products quality, MATCAVI is always looking for continuous improvement and the most performing components. Therefore, the above characteristics and components are indicative and can be changed without notice.